



POLYMAX INDUSTRIE-TECHNIEK B.V.

Tel: +31 (0)348-402900

Fax: + 31 (0)348-401597

POLYDEEN® ABSTÜTZPLATTEN

Abmessung in cm:	Gewicht (kg):	Durchschnitts-Kranbelastung:
40 x 40x4	6,1	10 tonnen
50 x 50x4	9,6	15 tonnen
60 x 60x4	13,8	20 tonnen
70 x 70x4	18,8	23 tonnen
80 x 80x4	24,5	25 tonnen
90 x 90x4	31,1	30 tonnen
50 x 50x5	12,0	18 tonnen
60 x 60x5	17,2	22 tonnen
70 x 70x5	23,5	25 tonnen
80 x 80x5	30,7	27 tonnen
90 x 90x5	38,8	35 tonnen
50 x 50x6	14,4	20 tonnen
60 x 60x6	20,7	25 tonnen
70 x 70x6	28,2	28 tonnen
80 x 80x6	36,8	30 tonnen
90 x 90x6	46,6	40 tonnen
100x100x6	57,6	50 tonnen
100x100x7	66,0	60 tonnen
100x100x8	76,0	70 tonnen
73,5x100x6	42,3	50 tonnen

SONDERPLATTEN MIT HANDGRIFFEN VOM ROSTFREI STAHL:		
125x100x7	84,0	80 tonnen
175x100x7	117,6	90 tonnen
125x100x8	96,0	90 tonnen
175x100x8	134,4	100 tonnen
200x125x8	192,0	120 tonnen

Die Abstützplatten sind ausgestattet mit 1 oder 2 Handgriffen.



POLYMAX INDUSTRIE-TECHNIEK B.V.

Tel: +31 (0)348-402900

Fax: + 31 (0)348-401597

POLYDEEN® ABSTÜTZPLATTEN

Abmessung in mm:	Durchschnitts-Kranbelastung:
Rund	
700x40	20 tonnen
700x50	25 tonnen
800x40	25 tonnen
800x50	30 tonnen
900x40	35 tonnen
900x50	40 tonnen
900x60	40 tonnen
1000x60	50 tonnen
1000x70	70 tonnen
1200x60	70 tonnen
1200x70	80 tonnen
1200x80	90 tonnen

POLYDEEN® FAHRPLATTEN

Abmessung in mm:	Gewicht:
2000 x 500 x 10	10 KG
2000 x 500 x 20	19 KG
3000 x 500 x 10	15 KG
3000 x 500 x 15	22 KG
3000 x 500 x 20	28 KG
3000 x 1000 x 10	30 KG
3000 x 1000 x 15	44 KG
3000 x 1000 x 20	56 KG
4000 x 1000 x 10	38 KG
4000 x 1000 x 15	58 KG
4000 x 1000 x 20	76 KG